



Gold Star
Series

VET-X

Veterinary Radiographic System



Unmatched
Performance
& Affordability

VET-X

VETERINARY SYSTEM

FEATURES AND SPECIFICATIONS

GENERATOR

30 kW power rating
 20 kHz high frequency technology
 Technique selection: mAs/kVp
 kVp range: 40-125
 mA range: 50-300
 mAs range: 0.8-300
 Digital display of mAs, mA and kVp
 Built-in tube protect system
 Automatic generator
 "Shut-off" circuit
 Includes 13 ft. line cable
 Operates from 230-250 VAC single phase electrical service

INTEGRATED TABLE & TUBE STAND

Enclosed, integrated radiographic table
 Tabletop: 53 in. x 24 in.
 Welded base construction
 Variable vertical tube travel
 Angulating tube mount, dial indicator and operator handgrips
 17" grid cabinet with tubestand interlock
 Animal restraining device
 Transformer mounting shelf
 8:1, 103 LPI grid
 Regular-duty manual tray
 Distance of Focal Spot from wall (assuming tubestand is wall mounted) is 22-7/8"

X-RAY TUBE

1.0-2.0 mm Focal Spot, 140 kHU, 90° housing

MANUAL COLLIMATOR

Manual light field collimator
 Field light "on" time -selectable 30, 60, 90 or 120 seconds
 Easy to operate with gloved hand

CABLES

10' high voltage cables with federal terminations

EXPOSURE SWITCH

Footswitch with 20' cord

Options, Upgrades & Extended Warranty Available upon request

Parts Warranty X-Ray system including X-Ray tube: 1-year

ASSURANCE SELECT HF VETERINARY SYSTEM

This fully-integrated, UL-listed table, tubestand and high frequency generator system requires as little as 11 square feet of floor space. Tube detents at 40 inches SID and angulates with mechanical lock. Grid cabinet and tubestand easily interlock for automatic alignment. Molded, rust-proof tray. Options include two sizes of floating table top, hands-free collimator light, latching prep, cassette bin.

SPECIFICATIONS

Space requirements
 Column height: 82.5"
 Fixed tabletop: 3" wide, 28" deep
 2-Way tabletop: 58" x 44", or 67" x 44"
 4-Way tabletop: 5" x 44"

